

DUAL OPERATIONAL AMPLIFIER

IL4580

GENERAL DESCRIPTION


The IL4580 is the dual operational amplifier, specially designer for improving the tone control, which is most suitable for the audio application.

Featuring noiseless, higher gain bandwidth, high output current and low distortion ratio, and it is most suitable not only for acoustic electronic parts of audio pre-amp and active filter, but also for the industrial measurement tools. It is also suitable for the head phone amp at higher output current, and further more, it can be applied for the handy type set operational amplifier of general purpose in application of low voltage single supply type which is properly biased of the input low voltage source.

FEATURES

- Operating Voltage ($\pm 2\text{ V} \sim \pm 18\text{ V}$)
- Wide Gain Bandwidth Product (15 MHz typ.)
- Slew Rate ($5\text{ V}/\mu\text{s}$ typ.)
- Bipolar Technology

BLOCK DIAGRAM




N SUFFIX
PLASTIC


D SUFFIX
SOIC

ORDERING INFORMATION
 IL4580N Plastic
 IL4580D SOIC
 $T_A = -40^\circ$ to 85° C
 for all packages.

PIN ASSIGNMENT



EQUIVALENT CIRCUIT (1/2 Show)



ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$)

Symbol	Parameter	Ratings	Unit
V^+/V^-	Supply Voltage	± 18	V
V_{ID}	Differential Input Voltage	30	V
V_{IC}	Input Voltage	$\pm 15^*$	V
I_O	Output Current	± 50	mA
Topr	Operation Temperature Range	$-40 \sim +85$	$^{\circ}\text{C}$
Tstg	Storage Temperature Range	$-60 \sim +125$	$^{\circ}\text{C}$

* For supply voltage less than ± 15 V, the absolute maximum input voltage is equal to the supply voltage.

** Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device.

These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied.


Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$, $V^+/V^- = \pm 15$)


Symbol	Parameter	Test Condition	Min	Max	Unit
V_{IO}	Input Offset Voltage	$R_S \leq 10 \text{ k}\Omega$	-	3	mV
I_{IO}	Input Offset Current		-	200	nA
I_B	Input Bias Current		-	500	nA
R_{IN}	Input Resistance		0.3	-	$\text{M}\Omega$
A_V	Large Signal Voltage Gain	$R_L \geq 2 \text{ k}\Omega$, $V_O = \pm 10 \text{ V}$	90	-	dB
V_{OM}	Output Voltage Swing	$R_L \geq 2 \text{ k}\Omega$	± 12	-	V
V_{ICM}	Input Common Mode Voltage Range		± 12	-	V
CMR	Common Mode Rejection Ratio	$R_S \leq 10 \text{ k}\Omega$	80	-	dB
SVR	Supply Voltage Rejection Ratio	$R_S \leq 10 \text{ k}\Omega$	80	-	dB
I_{CC}	Operating Current		-	9	mA
SR	Slew Rate	$R_L \geq 2 \text{ k}\Omega$	4	6	$\text{V}/\mu\text{s}$

■ TYPICAL CHARACTERISTICS


Maximum Output Voltage Swing vs. Load Resistance




Maximum Output Voltage Swing vs. Frequency




Output Voltage Swing vs. Output Current




Equivalent Input Noise Voltage vs. Frequency



Operating Current vs. Temperature




Output Voltage Swing vs. Temperature




■ TYPICAL CHARACTERISTICS


Input Offset Voltage vs. Temperature




Input Bias Current vs. Temperature




Maximum Output Voltage Swing vs. Operating Voltage




Operating Current vs. Operating Voltage







Total Harmonic Distortion vs. Output Voltage



Voltage Gain, Phase vs. Frequency



**N SUFFIX PLASTIC DIP
(MS - 001BA)**







$\oplus 0.25 (0.010) \text{ (M) T}$

Dimension, mm		
Symbol	MIN	MAX
A	8.51	10.16
B	6.1	7.11
C		5.33
D	0.36	0.56
F	1.14	1.78
G	2.54	
H	7.62	
J	0°	10°
K	2.92	3.81
L	7.62	8.26
M	0.2	0.36
N	0.38	

NOTES:

- Dimensions "A", "B" do not include mold flash or protrusions.
Maximum mold flash or protrusions 0.25 mm (0.010) per side.

**D SUFFIX SOIC
(MS - 012AA)**



$\oplus 0.25 (0.010) \text{ (M) T C (M)}$

Dimension, mm		
Symbol	MIN	MAX
A	4.8	5
B	3.8	4
C	1.35	1.75
D	0.33	0.51
F	0.4	1.27
G	1.27	
H	5.72	
J	0°	8°
K	0.1	0.25
M	0.19	0.25
P	5.8	6.2
R	0.25	0.5

NOTES:

- Dimensions A and B do not include mold flash or protrusion.
- Maximum mold flash or protrusion 0.15 mm (0.006) per side
for A; for B - 0.25 mm (0.010) per side.